QUICK REFERENCE GUIDE > HCI604TPB3

# 60cm 300 Series Induction Cooktop, 4 Zone, Low Current

## Black Glass



Replace your existing gas or ceramic cooktop with this Low Current Induction Cooktop. Enjoy the benefits of induction cooking, with the potential to use the existing wiring in your kitchen\*.

 19.7A rated current and 4.5kW rated power can be used with existing wiring\*

- With over nine heat settings, enjoy instant-response induction
- Surface remains cool-to-touch until cookware is placed on it
- · Made to match with a Haier wall oven in black glass

#### **DIMENSIONS**

Height	60 mm
Width	590 mm
Depth	520 mm

#### **FEATURES & BENEFITS**

#### **Low Current Induction**

This compact induction cooktop is the ideal option for replacing your gas or ceramic cooktop. With the potential to use existing wiring, this 19.7A rated current and 4.5kW rated power induction cooktop supports cost effective installations.

## Matching Design

The sleek black aesthetic matches the wider Haier family of appliances, pairing well with our black glass wall oven.

#### Rapid Heating For Busy Lives

Your induction cooktop is instant-response and heats rapidly, with precise control and a boost function for when you're in a hurry.

## Your Safety In Mind

The induction cooktop remains cool-to-touch until a pot or pan is placed on the surface, for safety in your kitchen.

### **Easy Cleaning**

Cleaning is easy thanks to a cooktop that stays cool around your cookware, avoiding baked-on spills. A quick wipe after use will help to keep your cooktop looking pristine.

## **Energy Efficiency**

Your induction cooktop only heats when cookware is placed on it, so less heat is wasted making it more energy-efficient than gas or electric cooking.

#### Intuitive Controls

With easy-to-use slide controls and a child lock for added safety. Choose from over nine heating settings, plus a boost function, for versatile cooking.

#### **SPECIFICATIONS**

## Controls

Timer

_	
Touch control glass interface	•

#### Performance

Heat settings	9 + Boost
Sensor in coils	•



QUICK REFERENCE GUIDE > HCI604TPB3 Date: 17.12.2024 > 2

_		
POWAR	requirem	ante
I OWCI	I Cquii Ciii	

AMP draw	19.7 A
Power cord length	1 m
Supply voltage	220 - 240 V

#### **Product dimensions**

Depth	520 mm
Height	60 mm
Installation cutout dimensions (Depth)	492 mm
Installation cutout dimensions (Width)	562 mm
Width	590 mm

# Safety

Child lock	•
Over heating alert	•
Over spillage alert	•
Surface hot indicators	•

# Warranty

Parts and labour	2 years

# Zone ratings

Left front power (Boost)	2000W (2600W)
Left rear power (Boost)	1500W (2000W)

Right front power (Boost) Right rear power (Boost)	1500W (2000W) 2000W (2600W)
Zones Cooking zones	4

SKU	61772

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © 2020 Haier Inc. All rights reserved.

## Other product downloads available at haier.com

## A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 0800 372273 Wwww.haier.com

